



2-Post Lift SGL35M | 3 x 400 V / 50 Hz

MPN: SGL35ME001-EU

GTIN: 4057612870312

Description

THE SGL35M IS THE HIGHLY EFFECTIVE HYDRAULIC 2-POST-LIFT

With the free-overhead/gantry structure and the compact dimensions it allows to save space in the workshop and at the same time is optimal for low ceiling areas. The manual lowering control ensures max. accuracy for the daily operations. The symmetric 3-stage-arms and the 3,5t capacity allow to lift a wide range of different vehicles (from micro cars to long wheel base sedans).

- Maximum safety: automatic support arm locking
- Low height: optimal use for low ceilings
- Minimum ceiling height: 3200 mm
- Quick fit and telescopic pads ensure high level of height adjustment.
- The electro-hydraulic design with only one power unit ensures energy-saving operation, low noise levels and effective work.
- The strong arms are automatically locked during lifting. When the platform is fully lowered, the locking mechanism is released automatically. The particularly fine locking mechanism and a manual unlocking function enhance the ease of operation.
- The free overhead structure makes the lift perfect for low ceiling workshops.
- The manual control ensures lowering with maximum working accuracy.
- Ground-guided, high-quality synchronization wire rope hoists ensure synchronization of the support arms.
- Easy to maintain
- The automatic mechanical safety latches integrated on both sides fix the lift carriage in case of emergency and thus ensure max. safety at the workplace.
- The electro-hydraulic design ensures quiet and effective operation.
- Each lifting column contains a high-quality, maintenance-free high-pressure cylinder and chain.



<https://rotarylif.eu/products/lifts-en/2-post-lifts-en/2-post-lift-sgl35m-3-x-400-v-50-hz/#comparison>



Media



2 Post Lift SGL35M BR 131254
Brochure



2 post lift SGL35M ceiling height DI
Image



2 Post Lift SGL35M BR 131256
Brochure



2 post lift SGL35M telescopic pads DI
Image



2 Post Lift SGL35M BR 131257
Brochure



2 post lift SGL35M power unit DI
Image



2 Post Lift SGL35M BR 131258
Brochure



2 post lift SGL35M energy saving operation DI
Image



2 Post Lift SGL35M BR 131260
Brochure



2 post lift SGL35M free overhead DI
Image



2 Post Lift SGL35M BR 131261
Brochure




2-Post Lift SGL35M | 1 x 230 V / 50 - 60 Hz
Image





Linked Products

Accessories



Base plates SGL35 | RAL7040
(2 pieces)




Rotary Adaptor Extension Kit 89 / 127 mm
4 x 89 mm, 4 x 127 mm, with 2...




Rotary Adaptor Extension Kit 200 mm
4 x 200 mm, with 2 organizer racks



U-support for delivery trucks/vans
(1 set / 4 pieces)



Pick-up set U-shaped
(1 set / 4 pieces)



Pick-up adapter Tesla
(1 set / 4 pieces)





Tech Data

	 2-Post Lift SGL35M 3 x 400 V / 50 Hz	 2-Post Lift SGL35M 1 x 230 V / 50 - 60 Hz
Mode of drive	electrohydraulic	electrohydraulic
Control	manually	manually
Type of installation	surface mounted	surface mounted
Rated load capacity	3500kg	3500kg
Lifting height max.	1828mm	1828mm
Lifting time	40s	40s
Rotary plate height min.	110mm	110mm
Rotary plate height max.	166mm	166mm
Column height	3160mm	3160mm
Drive-through width	2388mm	2388mm
Required ceiling height	3260mm	3260mm
Surface coating	powder coated	powder coated
Support arm design	symmetrical	symmetrical
Telescopability front support arms	3-fold	3-fold
Telescopability rear support arms	3-fold	3-fold
Support bracket length on the front min.	600mm	600mm
Support bracket length on the front max.	1280mm	1280mm
Support bracket length on the rear min.	600mm	600mm
Support bracket length on the rear max.	1280mm	1280mm
Driving power	1 x 2,2kW	1 x 2,2kW
Power supply	400 V 50 - 60 Hz	230 V 50 - 60 Hz
Phases	3	1
Width	3320mm	3320mm
Height	3160mm	3160mm