



Low-Rise Scissor Lift XS30N

MPN: XS30N

GTIN: 4057612751611

Description

The new short-stroke scissor lift XS30N impresses with its generously dimensioned platform length and width, which ensures that a wide range of vehicles can be accommodated. It covers the requirements in the field of tire and body service and is ideal for maintenance and work in the vehicle interior.



- Platform length and width matched to modern SUVs and vans
- Platform extension – Can be locked with just one hand
- Stable and secure
- Optional with cataphoresis coating
- The lift has a double hydraulic system and two torsion shafts that can hold the load safely in any situation.
- The standard CE stop ensures foot protection without a foot guard. This also enables underfloor installation.
- To enable flexible pick-up of both small and large vehicles, the XS30N has ramps that can be folded out on both sides, which ensure a total pick-up length of 2150 mm and can be locked in place with one hand. This also ensures that limousines as well as wide SUVs can be accommodated.
- The lift is completely assembled and ready for use immediately after connecting the hydraulics without major installation effort.
- The ramps with plastic rollers enable low-friction and gentle rolling on the workshop floor.
- The optional cataphoretic coating on the mounting platform and base frame provides additional corrosion protection for areas where salt is scattered.
- To enable flexible accommodation of both small and large vehicles, the XS30N has platform extensions that can be folded out on both sides and easily locked.
- Two independent hydraulic circuits with a total of 4 lifting cylinders make the absence of additional safety patches possible.
- The XS30N can be set up on any paved surface without foundation work, anchoring to the floor is possible but not necessary. The lift can be easily moved around in the workshop with the supplied mobile kit.
- The low drive-over height makes it easier to pick up vehicles with less ground clearance.



<https://rotarylif.eu/products/lifts-en/low-rise-lifts-en/low-rise-scissor-lift-xs30n/>



Media

	Low rise scissor lift xs30n 128783 Brochure			Scissor lift xs 30 vw beetle red Image	
	Low rise scissor lift xs30n 128784 Brochure			Scissor lift xs 30 low overpass height new Image	
	Low rise scissor lift xs30n 128785 Brochure			Scissor lift xs30n Image	
	Low rise scissor lift xs30n 128786 Brochure				
	Low rise scissor lift xs30n 128787 Brochure				
	Low rise scissor lift xs30n 128788 Brochure				
	Scissor lift xs30n Manuals				
	Scissor lift xs30n Manuals				
	Scissor lift xs30n Manuals				
	Scissor lift xs30n Manuals				
	Scissor lift xs30n Manuals				
	Scissor lift xs30n Manuals				
	Scissor lift xs 30 platform extension Image				
	Scissor lift xs30n safety latch Image				



Linked Products

Accessories




Rubber Bases T4
Heigh 80 mm, 4 pieces




Rubber Pads T4B
Height 40 mm, 4 pieces




Long ramps 860 mm, for sports cars
Hot-dip galvanized and powder-coated (1 set / 4 pieces)



Installation box for floor-level installation
Supporting boxes for folding ramps



Installation box for floor-level installation, incl. mounting frame
Galvanized



Cross beam kit RAL 7016
for vehicles with narrow pick-up points, 2 cross beam and...





Tech Data

	 Low-Rise Scissor Lift XS30N	 Low-Rise Scissor Lift XS30N-CAT
Mode of drive	electrohydraulic	electrohydraulic
Type of installation	floor mounted	floor mounted
Rated load capacity	3000kg	3000kg
Lifting height max.	1000mm	1000mm
Lifting time	30s	30s
Lowering time	20s	20s
Drive-on-height	105mm	105mm
Surface coating	powder coated	powder coated
Length of runways	1500 - 2150mm	1500 - 2150mm
Width of runways	530mm	530mm
Wheel free lift	not possible	not possible
Driving power	2,6kW	2,6kW
Power supply	230/400 V 50 Hz	230/400 V 50 Hz
Width	1980mm	1980mm
Weight	530kg	530kg