



## Twin Turbo impact wrench

Maximum loosening torque: 2200 Nm · Square, solid 12.5 mm (1/2 inch) · Powerful twin hammer mechanism

**Article no.:** 9012TT

**EAN:** 4000896226924

### Product information

#### Application:

Long service life and high efficiency in industrial and automotive applications.

Compact design, optimised for work in confined spaces

- Maximum loosening torque: 2200 Nm
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- Short design – only 128 mm
- HAZET Twin Turbo technology – high torques with compact design
- Innovative 8-blade air motor with 25% higher impact performance ensures maximum torques
- One-hand operation for right and left-handed users
- Powerful twin hammer mechanism
- Air connection inlet: Inside thread 12.91 mm (1/4")
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 948 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 110.7 db(A) Lp W
- Vibration acceleration: 8.69 m/s<sup>2</sup>
- Loosening torque (max) determined with screw size M: 16
- Forward and reverse: two-stage (forward), single-stage (reverse)
- Cold insulated handle
- Output: Square, solid 12.5 mm (1/2 inch)
- Net weight: 1.6 kg
- Tightening torque max.: 1356 Nm
- Maximum loosening torque: 2200 Nm
- Sound pressure level: 99.7 dB(A) Lp A
- Revolutions per minute: 8300
- Air requirement: 147.2 l/min (2.5 l/sec)

This website uses cookies, which are necessary for the technical operation of the website and are always set. Other cookies, which increase the usability of this website, serve for direct advertising or simplify interaction with other websites and social networks, will only be used with your consent.



## TECHNICAL DATA

- **Air inlet thread** : Inside thread 12.91 mm (1/4")
- **Air requirement l/min** : 147.2 l/min
- **Coupler plug** : Nominal size 7.2 (included)
- **Forward/reverse** : two-stage (forward), single-stage (reverse)
- **Handle** : Cold insulated handle
- **Hose diameter (recommended)** : 10 mm
- **Loosening torque max.** : 2200 Nm
- **Net weight** : 1.6 kg
- **Output** : ■ 12,5 = 1/2"
- **Recommended torque** : 948 Nm
- **Revolutions per minute** : 8300
- **Screw size M** : 16 M
- **Sound power level** : 110.7 db(A) Lp W
- **Sound pressure level** : 99.7 dB(A) Lp A
- **Striking mechanism (type)** : Powerful twin hammer mechanism
- **Tightening torque max.** : 1356 Nm
- **Vibration acceleration** : 8.69 m/s<sup>2</sup>
- **Working pressure (bar)** : 6.3 bar

This website uses cookies, which are necessary for the technical operation of the website and are always set. Other cookies, which increase the usability of this website, serve for direct advertising or simplify interaction with other websites and social networks, will only be used with your consent.